3G/4G LNS

NAT


CA
AAA
SNC
一级行

```
interface GigabitEthernet 0/0/8
 ip address 20.1.1.1 255.255.255.0   ----       IP
 duplex auto
 speed auto
 media-type basex auto    ----

interface GigabitEthernet 0/0/1.1
 encapsulation dot1Q 1   ---              vlan
 ip access-group 101 in   ---                acl
 ip access-group 101 out
 ip address 1.1.1.1 255.255.255.0  ---      IP
```

router ospf 1 ---- ospf

bfd all-interfaces ---- bfd

network 1.1.1.0 0.0.0.255 area 1 ----- 0 area

network 1.1.2.0 0.0.0.255 area 1

network 1.1.199.0 0.0.0.255 area 10 ----- 0 area

network 1.1.200.0 0.0.0.255 area 10

network 20.1.1.0 0.0.0.255 area 0 ----- area 0

➢

```
interface GigabitEthernet 0/0/1.1
 encapsulation dot1Q 1
 ip access-group 101 in
 ip access-group 101 out
 ip address 1.1.1.1 255.255.255.0
bfd interval 50 min_rx 50 multiplier 3  ---          BFD
 no bfd echo   ---    !  `                          н P
```



➢

1. IP

```
ip access-list extended q1
 10 permit ip 51.46.1.0 0.0.0.255 any
 20 permit ip 51.46.2.0 0.0.0.255 any
ip access-list extended q2
 10 permit ip 51.46.3.0 0.0.0.255 any
 20 permit ip 51.46.4.0 0.0.0.255 any
ip access-list extended q3
 10 permit ip 51.46.5.0 0.0.0.255 any
 20 permit ip 51.46.6.0 0.0.0.255 any
ip access-list extended q4
 10 permit ip 51.46.7.0 0.0.0.255 any
 20 permit ip 51.46.8.0 0.0.0.255 any
```

2. user-queue 1000M

user-queue 1 inbound

cir 1000000 pir 1000000

3. traffic classifier acl classifier



4. traffic behavior behavior

traffic behavior 1

user-queue 1 inbound

service-class af1 color green

traffic behavior 2

user-queue 1 inbound

service-class af2 color green

traffic behavior 3

user-queue 1 inbound

service-class af3 color green

traffic behavior 4

user-queue 1 inbound

service-class cs6 color green



5. traffic policy classifier behavior

traffic policy hqos

classifier 1 behavior 1 precedence 1

classifier 2 behavior 2 precedence 2

classifier 3 behavior 3 precedence 3

classifier 4 behavior 4 precedence 4

interface GigabitEthernet 0/0/8

ip address 20.1.1.1 255.255.255.0

traffic-policy hqos inbound

duplex auto

speed auto

media-type basex auto

GR

GR

Restarter

Helper Restarter Restarter

OSPF-GR Restarter helper

helper

RSR7708(config)#router ospf 2

RSR7708(config-router)#graceful-restart

- ping IP
- show ip ospf neighber OSPF
- show bfd neighber BFD
- show ip ospf GR
- sh user-queue statistics 1 inbound HQOS

1 user-queue inbound in

3G/4G LNS

NAT

3G/4G LNS

NAT

3G/4G LNS

VPDN IPSEC VPN

RSR30-X

SM1

3G AAA AAA

IP

IPSEC LNS 3G







AAA

VPDN

IPSEC

www.ruijie.com.cn

3G/4G LNS

➢

HNM-SEC SM1

HNM-SEC

➢

aaa new-model // AAA

aaa authentication ppp default group radius local // PPP Radius

local Radius Radius

radius-server host 30.160.14.16 auth-port 1645 acct-port 1646 key xxxx //

Radius

ip route x.x.x.x x.x.x.x x.x.x.x //

3G/4G LNS

➢

VPDN

```
vpdn enable                          //    vpdn
vpdn-group LNS                       //    vpdn          LNS
 accept-dialin                       //
  protocol l2tp                      //vpdn    l2tp
  virtual-template 1                 //
 l2tp tunnel authentication          //    L2TP
 l2tp tunnel password xxxx           //
```

loopback

```
interface Loopback 1
 ip address 30.160.230.1 255.255.255.0
```

VPDN

```
interface Virtual-Template 1         //
 ppp authentication chap             //    PPP
 ip unnumbered Loopback 1            //
```

3G/4G LNS

➢

crypto dynamic-map test 1

reverse-route // RRI

Route ospf 1

Network x.x.x.x x.x.x.x area x

redistribute static subnets // RRI

3G/4G LNS

➢

show vpdn 3G

ping 3G

show crypto ipsec sa IPSEC

show ip route

LNS ping 3G



NAT

NAT

inside/outside



NAT

ip nat inside source static 1.1.1.1 10.1.1.1

ip route 1.1.1.0 255.255.255.0 100.0.0.2

ip nat outside source static 2.2.2.1 20.2.2.1



PC
IP:2.2.2.1
IP 20.2.2.1

IP:1.1.1.1
IP 10.1.1.1

outside
interface GigabitEthernet 0/0/1
ip address 200.0.0.1 255.255.255.0
ip nat

inside
interface GigabitEthernet 0/0/2
ip address 100.0.0.1 255.255.255.0
ip nat

www.ruijie.com.cn

www.ruijie.com.cn/service.aspx

support.ruijie.com.cn

webchat.ruijie.com.cn

4008-111-000